



TB-1503

导线截面 wire section: 0.5-1.5mm²

额定电流/电压 rated current/voltage: 15A/600V

宽/高/厚 wide/high/thick: 46.5/22/17.5mm



TB-1504

导线截面 wire section: 0.5-1.5mm²

额定电流/电压 rated current/voltage: 15A/600V

宽/高/厚 wide/high/thick: 55.5/22/17.5mm



TB-1505

导线截面 wire section: 0.5-1.5mm²

额定电流/电压 rated current/voltage: 15A/600V

宽/高/厚 wide/high/thick: 63/22/17.5mm



TB-1506

导线截面 wire section: 0.5-1.5mm²

额定电流/电压 rated current/voltage: 15A/600V

宽/高/厚 wide/high/thick: 73.5/22/17.5mm



TB-1510

导线截面 wire section: 0.5-1.5mm²

额定电流/电压 rated current/voltage: 15A/600V

宽/高/厚 wide/high/thick: 103/22/17.5mm



TB-1512

导线截面 wire section: 0.5-1.5mm²

额定电流/电压 rated current/voltage: 15A/600V

宽/高/厚 wide/high/thick: 128.5/22/17.5mm



TB-2503

导线截面 wire section: 0.5-2.5mm²

额定电流/电压 rated current/voltage: 25A/600V

宽/高/厚 wide/high/thick: 55/30/19mm



TB-2504

导线截面 wire section: 0.5-2.5mm²

额定电流/电压 rated current/voltage: 25A/600V

宽/高/厚 wide/high/thick: 67/30/19mm



TB-2505

导线截面 wire section: 0.5-2.5mm²

额定电流/电压 rated current/voltage: 25A/600V

宽/高/厚 wide/high/thick: 79/30/19mm



TB-2506

导线截面 wire section: 0.5-2.5mm²

额定电流/电压 rated current/voltage: 25A/600V

宽/高/厚 wide/high/thick: 91/30/19mm



TB-2510

导线截面 wire section: 0.5-2.5mm²

额定电流/电压 rated current/voltage: 25A/600V

宽/高/厚 wide/high/thick: 140/30/19mm



TB-2512

导线截面 wire section: 0.5-2.5mm²

额定电流/电压 rated current/voltage: 25A/600V

宽/高/厚 wide/high/thick: 163/30/19mm



TB-4503

导线截面 wire section: 1.5-4mm²

额定电流/电压 rated current/voltage: 45A/600V

宽/高/厚 wide/high/thick: 70/38/23.5mm



TB-4504

导线截面 wire section: 1.5-4mm²

额定电流/电压 rated current/voltage: 45A/600V

宽/高/厚 wide/high/thick: 85/38/23.5mm



TB-4505

导线截面 wire section: 1.5-4mm²

额定电流/电压 rated current/voltage: 45A/600V

宽/高/厚 wide/high/thick: 102.5/38/23.5mm



TB-4506

导线截面 wire section: 1.5-4mm²

额定电流/电压 rated current/voltage: 45A/600V

宽/高/厚 wide/high/thick: 120.5/38/23.5mm



TB-4512

导线截面 wire section: 1.5-4mm²

额定电流/电压 rated current/voltage: 45A/600V

宽/高/厚 wide/high/thick: 222/38/23.5mm



TYPE	RATING	NUMBER OF POLES	DIMENSIONS (mm)						
			L	L1	A	B	C	D	E
TB-603	600V 60A	3	70.5	65.5	15.5	18	M6	38	31
TB-604		4	93.5	82.5	15.5	18	M6	38	31
TB-606		6	129	118	15.5	18	M6	38	31
TB-1003	600V 100A	3	86.5	75.5	22	20	M6	43.5	35
TB-1004		4	108	96	22	20	M6	43.5	35
TB-1006		6	153	140	22	20	M6	43.5	35

