



SIMATIC S7-1500, analog input module AI 8xU/R/RTD/TC HF, 16 bit resolution, up to 21 bit resolution for RTD and TC, accuracy 0.1%, 8 channels in groups of 1, common mode voltage: 30 V AC/60 V DC, Diagnostics, hardware interrupts Scalable temperature measuring range, thermocouple type C, calibrate in RUN Incl. infeed element, shield bracket and shield terminal: Front connector (screw terminals or push-in) to be ordered separately

General information	
Product type designation	AI 8xU/R/RTD/TC HF
HW functional status	FS01
Firmware version	V1.1.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Measuring range scalable</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Scalable measured values</li> </ul>	No
<ul style="list-style-type: none"> <li>Adjustment of measuring range</li> </ul>	No
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated as of version</li> </ul>	V14 / -
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated as of version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PROFIBUS as of GSD version/GSD revision</li> </ul>	V1.0 / V5.1
<ul style="list-style-type: none"> <li>PROFINET as of GSD version/GSD revision</li> </ul>	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> <li>Oversampling</li> </ul>	No
<ul style="list-style-type: none"> <li>MSI</li> </ul>	Yes

CiR – Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	55 mA; with 24 V DC supply
Power	
Power available from the backplane bus	0.85 W
Power loss	
Power loss, typ.	1.9 W
Analog inputs	
Number of analog inputs	8; Plus one additional RTD (reference) channel
<ul style="list-style-type: none"> <li>• For voltage measurement</li> </ul>	8; Plus one additional RTD (reference) channel
<ul style="list-style-type: none"> <li>• For resistance/resistance thermometer measurement</li> </ul>	8; Plus one additional RTD (reference) channel
<ul style="list-style-type: none"> <li>• For thermocouple measurement</li> </ul>	8; Plus one additional RTD (reference) channel
permissible input voltage for voltage input (destruction limit), max.	20 V
Constant measurement current for resistance-type transmitter, typ.	150 Ohm, 300 Ohm, 600 Ohm, Cu10, Cu50, Cu100, Ni10, Ni100, Ni120, Ni200, Pt10, Pt50, Pt100, Pt200 climate: 1 mA; 6 kOhm, Ni500, Ni1000, LG-Ni1000, Pt200 standard, Pt500, Pt1000, PTC: 0.25 mA
Technical unit for temperature measurement adjustable	Yes; °C/°F/K
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> <li>• 0 to +5 V</li> </ul>	No
<ul style="list-style-type: none"> <li>• 0 to +10 V</li> </ul>	No
<ul style="list-style-type: none"> <li>• 1 V to 5 V</li> </ul>	No
<ul style="list-style-type: none"> <li>• -1 V to +1 V</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Input resistance (-1 V to +1 V)</li> </ul>	10 MΩ
<ul style="list-style-type: none"> <li>• -10 V to +10 V</li> </ul>	No
<ul style="list-style-type: none"> <li>• -2.5 V to +2.5 V</li> </ul>	No
<ul style="list-style-type: none"> <li>• -25 mV to +25 mV</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Input resistance (-25 mV to +25 mV)</li> </ul>	10 MΩ
<ul style="list-style-type: none"> <li>• -250 mV to +250 mV</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Input resistance (-250 mV to +250 mV)</li> </ul>	10 MΩ

• -5 V to +5 V	No
• -50 mV to +50 mV	Yes
• Input resistance (-50 mV to +50 mV)	10 MΩ
• -500 mV to +500 mV	Yes
• Input resistance (-500 mV to +500 mV)	10 MΩ
• -80 mV to +80 mV	Yes
• Input resistance (-80 mV to +80 mV)	10 MΩ
<b>Input ranges (rated values), currents</b>	
• 0 to 20 mA	No
• -20 mA to +20 mA	No
• 4 mA to 20 mA	No
<b>Input ranges (rated values), thermocouples</b>	
• Type B	Yes
• Input resistance (Type B)	10 MΩ
• Type C	Yes
• Input resistance (Type C)	10 MΩ
• Type E	Yes
• Input resistance (Type E)	10 MΩ
• Type J	Yes
• Input resistance (type J)	10 MΩ
• Type K	Yes
• Input resistance (Type K)	10 MΩ
• Type L	No
• Type N	Yes
• Input resistance (Type N)	10 MΩ
• Type R	Yes
• Input resistance (Type R)	10 MΩ
• Type S	Yes
• Input resistance (Type S)	10 MΩ
• Type T	Yes
• Input resistance (Type T)	10 MΩ
• Type TXK/TXK(L) to GOST	Yes
• Input resistance (Type TXK/TXK(L) to GOST)	10 MΩ
<b>Input ranges (rated values), resistance thermometer</b>	
• Cu 10	Yes; Standard/climate
• Input resistance (Cu 10)	10 MΩ
• Cu 10 according to GOST	Yes; Standard/climate
• Input resistance (Cu 10 according to GOST)	10 MΩ
• Cu 50	Yes; Standard/climate
• Input resistance (Cu 50)	10 MΩ
• Cu 50 according to GOST	Yes; Standard/climate

• Input resistance (Cu 50 according to GOST)	10 MΩ
• Cu 100	Yes; Standard/climate
• Input resistance (Cu 100)	10 MΩ
• Cu 100 according to GOST	Yes; Standard/climate
• Input resistance (Cu 100 according to GOST)	10 MΩ
• Ni 10	Yes; Standard/climate
• Input resistance (Ni 10)	10 MΩ
• Ni 10 according to GOST	Yes; Standard/climate
• Input resistance (Ni 10 according to GOST)	10 MΩ
• Ni 100	Yes; Standard/climate
• Input resistance (Ni 100)	10 MΩ
• Ni 100 according to GOST	Yes; Standard/climate
• Input resistance (Ni 100 according to GOST)	10 MΩ
• Ni 1000	Yes; Standard/climate
• Input resistance (Ni 1000)	10 MΩ
• Ni 1000 according to GOST	Yes; Standard/climate
• Input resistance (Ni 1000 according to GOST)	10 MΩ
• LG-Ni 1000	Yes; Standard/climate
• Input resistance (LG-Ni 1000)	10 MΩ
• Ni 120	Yes; Standard/climate
• Input resistance (Ni 120)	10 MΩ
• Ni 120 according to GOST	Yes; Standard/climate
• Input resistance (Ni 120 according to GOST)	10 MΩ
• Ni 200	Yes; Standard/climate
• Input resistance (Ni 200)	10 MΩ
• Ni 200 according to GOST	Yes; Standard/climate
• Input resistance (Ni 200 according to GOST)	10 MΩ
• Ni 500	Yes; Standard/climate
• Input resistance (Ni 500)	10 MΩ
• Ni 500 according to GOST	Yes; Standard/climate
• Input resistance (Ni 500 according to GOST)	10 MΩ
• Pt 10	Yes; Standard/climate
• Input resistance (Pt 10)	10 MΩ
• Pt 10 according to GOST	Yes; Standard/climate
• Input resistance (Pt 10 according to GOST)	10 MΩ
• Pt 50	Yes; Standard/climate
• Input resistance (Pt 50)	10 MΩ
• Pt 50 according to GOST	Yes; Standard/climate
• Input resistance (Pt 50 according to GOST)	10 MΩ
• Pt 100	Yes; Standard/climate
• Input resistance (Pt 100)	10 MΩ

• Pt 100 according to GOST	Yes; Standard/climate
• Input resistance (Pt 100 according to GOST)	10 MΩ
• Pt 1000	Yes; Standard/climate
• Input resistance (Pt 1000)	10 MΩ
• Pt 1000 according to GOST	Yes; Standard/climate
• Input resistance (Pt 1000 according to GOST)	10 MΩ
• Pt 200	Yes; Standard/climate
• Input resistance (Pt 200)	10 MΩ
• Pt 200 according to GOST	Yes; Standard/climate
• Input resistance (Pt 200 according to GOST)	10 MΩ
• Pt 500	Yes; Standard/climate
• Input resistance (Pt 500)	10 MΩ
• Pt 500 according to GOST	Yes; Standard/climate
• Input resistance (Pt 500 according to GOST)	10 MΩ
<b>Input ranges (rated values), resistors</b>	
• 0 to 150 ohms	Yes
• Input resistance (0 to 150 ohms)	10 MΩ
• 0 to 300 ohms	Yes
• Input resistance (0 to 300 ohms)	10 MΩ
• 0 to 600 ohms	Yes
• Input resistance (0 to 600 ohms)	10 MΩ
• 0 to 3000 ohms	No
• 0 to 6000 ohms	Yes
• Input resistance (0 to 6000 ohms)	10 MΩ
• PTC	Yes
• Input resistance (PTC)	10 MΩ
<b>Thermocouple (TC)</b>	
<b>Temperature compensation</b>	
— parameterizable	Yes
— internal temperature compensation	Yes
— external temperature compensation via RTD	Yes
— Compensation for 0 °C reference point temperature	Yes; fixed value can be set
— Reference channel of the module	Yes; 9th channel that can be used as a genuine 9th RTD channel regardless of the parameterization of the other channels, or that can be used for compensation in the case of TC measurement
<b>Cable length</b>	
• shielded, max.	800 m; at U; 200 m at R/RTD/TC
<b>Analog value generation for the inputs</b>	
<b>Integration and conversion time/resolution per channel</b>	

- Resolution with overrange (bit including sign), max.
- Integration time, parameterizable
- Integration time (ms)
- Basic conversion time, including integration time (ms)
  - additional conversion time for wire-break monitoring
- Interference voltage suppression for interference frequency f1 in Hz
- Basic execution time of the module (all channels released)

21 bit; For measuring mode RTC and TC when using the function "Scalable temperature measuring range" (32 bit REAL format); 16 bit for measuring mode R and U; 16 bit for all measuring modes when using the S7 format (16 bit INTEGER)

Yes

Fast mode: 2.5 / 16.67 / 20 / 100 ms, standard mode: 7.5 / 50 / 60 / 300 ms

Fast mode: 4 / 18 / 22 / 102 ms; Standard mode: 9 / 52 / 62 / 302 ms

Thermocouples, 150 Ohm, 300 Ohm, 600 Ohm, Cu10, Cu50, Cu100, Ni10, Ni100, Ni120, Ni200, Pt10, Pt50, Pt100: 4 ms; 6 kOhm, Ni500, Ni1000, LG-Ni1000, Pt200, Pt500, Pt1000: 13 ms  
400 / 60 / 50 / 10 Hz

Corresponds to the channel with the highest basic conversion time

#### Smoothing of measured values

- parameterizable
- Step: None
- Step: low
- Step: Medium
- Step: High

Yes

Yes

Yes

Yes

Yes

#### Encoder

##### Connection of signal encoders

- for voltage measurement
- for current measurement as 2-wire transducer
- for current measurement as 4-wire transducer
- for resistance measurement with two-wire connection
- for resistance measurement with three-wire connection
- for resistance measurement with four-wire connection

Yes

No

No

Yes

Yes; All measuring ranges except PTC; internal compensation of the cable resistances

Yes; All measuring ranges except PTC

#### Errors/accuracies

Linearity error (relative to input range), (+/-)	0.02 %
Temperature error (relative to input range), (+/-)	0.005 %/K
Crosstalk between the inputs, max.	-80 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.02 %
Temperature error of internal compensation	±1,5 °C

##### Operational error limit in overall temperature range

- Voltage, relative to input range, (+/-) 0.1 %
- Resistance, relative to input range, (+/-) 0.1 %

<ul style="list-style-type: none"> <li>Resistance thermometer, relative to input range, (+/-)</li> <li>Thermocouple, relative to input range, (+/-)</li> </ul>	<p>Cuxxx Standard: ±0.5 K, Cuxxx Klima: ±0.5 K, Ptxxx Standard: ±1 K, Ptxxx Klima: ±0.5 K, Nixxx Standard: ±0.5 K, Nixxx Klima: ±0.3 K</p> <p>Type B: &gt; 600 °C ±2 K, Type E: &gt; -200 °C ±1 K, Type J: &gt; -210 °C ±1 K, Type K: &gt; -200 °C ±2 K, Type N: &gt; -200 °C ±2 K, Type R: &gt; 0 °C ±2 K, Type S: &gt; 0 °C ±2 K, Type T: &gt; -200 °C ±1 K, Type C: ±4 K, Type TXK/TXK(L): ±1 K</p>
<b>Basic error limit (operational limit at 25 °C)</b>	
<ul style="list-style-type: none"> <li>Voltage, relative to input range, (+/-)</li> <li>Resistance, relative to input range, (+/-)</li> <li>Resistance thermometer, relative to input range, (+/-)</li> <li>Thermocouple, relative to input range, (+/-)</li> </ul>	<p>0.05 %</p> <p>0.05 %</p> <p>Cuxxx Standard: ±0.3 K, Cuxxx Klima: ±0.2 K, Ptxxx Standard: ±0.5 K, Ptxxx Klima: ±0.2 K, Nixxx Standard: ±0.3 K, Nixxx Klima: ±0.15 K</p> <p>Type B: &gt; 600 °C ±1 K, Type E: &gt; -200 °C ±0.5 K, Type J: &gt; -210 °C ±0.5 K, Type K: &gt; -200 °C ±1 K, Type N: &gt; -200 °C ±1 K, Type R: &gt; 0 °C ±1 K, Type S: &gt; 0 °C ±1 K, Type T: &gt; -200 °C ±0.5 K, Type C: ±2 K, Type TXK/TXK(L): ±0.5 K</p>
<b>Interference voltage suppression for <math>f = n \times (f_1 \pm 1 \%)</math>, <math>f_1</math> = interference frequency</b>	
<ul style="list-style-type: none"> <li>Series mode interference (peak value of interference &lt; rated value of input range), min.</li> <li>Common mode voltage, max.</li> <li>Common mode interference, min.</li> </ul>	<p>80 dB; in the Standard operating mode, 40 dB in the Fast operating mode</p> <p>60 V DC/30 V AC</p> <p>80 dB</p>
<b>Isochronous mode</b>	
Isochronous operation (application synchronized up to terminal)	No
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> <li>Limit value alarm</li> </ul>	<p>Yes</p> <p>Yes; two upper and two lower limit values in each case</p>
<b>Diagnostic messages</b>	
<ul style="list-style-type: none"> <li>Monitoring the supply voltage</li> <li>Wire-break</li> <li>Overflow/underflow</li> </ul>	<p>Yes</p> <p>Yes; Only with TC, R, RTD</p> <p>Yes</p>
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>RUN LED</li> <li>ERROR LED</li> <li>Monitoring of the supply voltage (PWR-LED)</li> <li>Channel status display</li> <li>for channel diagnostics</li> <li>for module diagnostics</li> </ul>	<p>Yes; Green LED</p> <p>Yes; Red LED</p> <p>Yes; Green LED</p> <p>Yes; Green LED</p> <p>Yes; Red LED</p> <p>Yes; Red LED</p>
<b>Potential separation</b>	
Potential separation channels	

- between the channels
- between the channels, in groups of
- between the channels and backplane bus
- between the channels and the power supply of the electronics

Yes  
1  
Yes  
Yes

### Permissible potential difference

between different circuits

60 V DC/30 V AC; insulation rated for 120 V AC basic insulation: between the channels and the supply voltage L+; between the channels and the backplane bus; between the channels

### Isolation

Isolation tested with

2 000 V DC between the channels and the supply voltage L+; 2 000 V DC between the channels and the backplane bus; 2 000 V DC between the channels; 707 V DC (type test) between the supply voltage L+ and the backplane bus

### Standards, approvals, certificates

Suitable for applications according to AMS 2750

Yes; Declaration of Conformity, see online support entry 109757262

Suitable for applications according to CQI-9

Yes; Based on AMS 2750 E

### Ambient conditions

Ambient temperature during operation

- horizontal installation, min.
- horizontal installation, max.
- vertical installation, min.
- vertical installation, max.

0 °C  
60 °C  
0 °C  
40 °C

### Decentralized operation

Prioritized startup

Yes

### Dimensions

Width

35 mm

Height

147 mm

Depth

129 mm

### Weights

Weight, approx.

290 g

### Other

Note:

For the R/RDT three-wire measurement, the conductor compensation is made alternating with the measurement. This then requires two module cycles for a measured value.

**last modified:**

10/22/2018