



Commercial status

End of Commercialisation : AUG 25, 2017

⚠ End of Commercialisation

Main

Product or component type	Switch
Device short name	I
Device application	Control
Poles description	3P
Utilisation category	AC-22A
Suitability for isolation	Yes

Complementary

[Ie] rated operational current	32 A at 415 V AC 50/60 Hz
[Ue] rated operational voltage	415 V AC 50/60 Hz
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to EN/IEC 60669-2-4
[Uimp] rated impulse withstand voltage	4 KV
Control type	Toggle
Local signalling	ON/OFF indication
Contact position indicator	Yes
Mounting mode	Fixed
Mounting support	DIN rail
9 mm pitches	4
Colour	Grey
Mechanical durability	300000 Cycles
Electrical durability	30000 Cycles
Connections - terminals	Tunnel type terminals - 1 x 1.5...1 x 10 mm ² - flexible Tunnel type terminals - 1 x 1.5...1 x 10 mm ² - rigid Tunnel type terminals - 2 x 2.5 mm ² - flexible Tunnel type terminals - 2 x 2.5 mm ² - rigid Tunnel type terminals - 2 x 4 mm ² - flexible Tunnel type terminals - 2 x 4 mm ² - rigid
Wire stripping length	9 Mm
Tightening torque	3.5 N.M

Environment

Standards	EN/IEC 60669-2-4
IP degree of protection	IP4
Pollution degree	2
Tropicalisation	2

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6 Cm
Package 1 Width	3.5 Cm
Package 1 Length	7.6 Cm
Package 1 Weight	0.118 Kg

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **End of commerc. - Block**