



## Data sheet for Smart Line Modules Booksize

Article No. : **6SL3130-6AE21-0AB1**

Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

Electrical data	
<b>Input</b>	
Number of phases	3 AC
Line voltage	342 ... 528 V
Line frequency	47 ... 63 Hz
Short-circuit strength <sup>1)</sup>	65 kA
<b>Line power factor</b>	
Fundamental power factor, minimal	.96
Total	0.65 ... 0.90
Overvoltage category	Class III
<b>DC link voltage<sup>2)</sup></b>	
DC-link voltage	1.35 × line voltage
Electronics power supply with DC	24 V (-15 % / 20 %)

Connections	
<b>Line side</b>	
Design	screw-type terminal (X1)
Conductor cross-section	2.5 ... 6 mm <sup>2</sup> (AWG 14 ... AWG 10)
PE conductor	M5 screw
Shield connecting kit	Cable shield connection plate integrated into the connector
<b>Line length, max.</b>	
Shielded	350 m (1,148.29 ft)
Unshielded	560 m (1,837.27 ft)

Mechanical data	
Degree of protection	IP20 / UL open type
Type of construction	Booksize
Net weight	4.8 kg (10.58 lb)
<b>Dimensions</b>	
Width	50 mm (1.97 in)
Height	380 mm (14.96 in)
Depth	270 mm (10.63 in)

Standards	
Compliance with standards	CE, cULus

Rated data	
<b>Infeed power</b>	
Rated value	10.0 kW (10.0 hp)
for S6 duty	13.0 kW
Maximum	20.0 kW
<b>Regenerative feedback power</b>	
Rated value	10.0 kW (10.0 hp)
for S6 duty	13.0 kW
Maximum	20.0 kW
<b>DC-link current</b>	
at 540 V DC	18.5 A
at 600 V DC	16.6 A
for S6 duty	22.0 A
Maximum	33.2 A
<b>Input current</b>	
at 380 V AC 3-phase	17.0 A
at 400 V AC 3-phase	16.2 A
at 480 V AC 3-phase	12.8 A
at 400 V S6 duty	21.1 A
at 400 V, maximum	31.2 A
Current requirement at 24 V DC, maximum	0.90 A
<b>Ampacity of the busbars</b>	
for electronics power supply at 24 V DC	20 A
for DC-link connection	100 A
<b>DC link capacitance</b>	
of the Smart Line Module	330 µF
of the drive system, maximum	6,000 µF
General technical specifications	
Sound pressure level	60 dB
Losses <sup>4)</sup>	0.140 kW
Ambient conditions	
Ambient temperature in operation	0 ... 40 °C (32 ... 104 °F)
Cooling air throughput	0.008 m <sup>3</sup> /s (0.283 ft <sup>3</sup> /s)
Installation altitude	1,000 m (3,280.84 ft)
Type of cooling	Internal air cooling
RI suppression	Standard: No radio interference suppression; With line filter: Category C2 to EN 61800-3 Total cable length up to 350 m (1148 ft) (shielded)

<sup>1)</sup>in conjunction with the recommended Class J fuse, or circuit breaker according to UL489 / CSA 22.2 No. 5-02

<sup>2)</sup>The DC link voltage is maintained at the mean value of the rectified line voltage.

<sup>4)</sup>Power loss of the Smart Line Module with rated power including losses of the 24 V DC electronics power supply