

Product type designation

C-PLUG

C-plug, removable data storage medium for simple device replacement in case of fault, for recording configuration or project engineering and application data, can be used in the following SIMATIC NET products with C-plug slot: SCALANCE X-200, X-300, X-400, S-600, CP443-1 Advanced, CP343-1 Advanced, CP343-1 ERPC, IE/PB Link PNIO, IE/AS-i Link PNIO, DP/AS-i Link Advanced



Ambient conditions

Ambient temperature	
• during operation	-40 ... +75 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weights

Width	24.3 mm
Height	17 mm
Depth	8.1 mm
Net weight	5 g
design of the removable storage	
• C-PLUG	Yes
• KEY-PLUG	No
Product feature / conformal coating	No

Product features, product functions, product components / general

Storage capacity	32 Mibyte
------------------	-----------

Standards, specifications, approvals

Reference code

- according to IEC 81346-2:2018

CFA

Further information / Internet-Links

Internet-Link

- to website: TIA Selection Tool
- to website: Selector SIMATIC NET SELECTION TOOL
- to the website: IWLAN
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/tia-selection-tool>

<http://www.siemens.com/snst>

<http://www.siemens.com/iwlan>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

07/13/2020