



CIRCUIT BREAKER T55 230/400V, 6KA,
1-POLE, C, 4A

General technical data:		
type of voltage		AC/DC
Mounting depth	mm	55
Current / for AC / rated value	A	4
Tripping characteristic class		C
Supply voltage / for AC / rated value	V	400
Switching capacity current		
• in accordance with IEC 60947-2 / rated value	kA	10
• acc. to EN 60898 / rated value	kA	6
Number of pitch units for width		1
Degree of pollution		3
Overvoltage class		3

Certificates/approvals:

General Product Approval				Declaration of Conformity
 CSA	 GOST	 KETI	 VDE	 EG-Konf.
Test Certificates		Shipping Approval	other	
Special Test Certificate	Type Test Certificates/Test Report	 LRS	other	Environmental Confirmations

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SX2104-7/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SX2104-7

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Sep 24, 2012