

Catalogue No: **1769-OB16**
COMPACTLOGIX 16DO 20.4-26.4V DC MODULE

Automation Systems > Modular Programmable Controllers > Compact PLC Systems > Allen-Bradley Bulletin 1769
CompactLogix™ > CompactLogix™ I/O Modules > CompactLogix™ Digital I/O Modules



Representative Photo Only
(actual product may vary based on configuration selections)

CompactLogix 16 Point 24V DC Sourcing Output Module

- AC and DC modules available
- I/O density from 8 to 32 points per module
- Solid state and relay contact output modules available
- High speed input modules
- Input filtering is standard
- Optical isolation available

SPECIFICATIONS	
Product Series	CompactLogix (Bul. 1768 / 1769)
Component Type PLC & I/O	Digital Output Module
Number of Digital Outputs	16 qty
Digital Output Type	24V DC Sourcing (NPN) type
Type, Digital Output	24V DC Source type
Digital Output Range	20.4 ... 26.4V DC
Rated Current per Digital Output, Max	0.5 A max, per DO
Rated Current per Module, Max	4 A max, per module
Operating Temperature, Max	60 °C max
Operating Temperature, Min	0 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
Humidity Type	Non-condensing

REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-