SIEMENS

Product data sheet

3TF2010-0AG2



CONTACTOR, SIZE 00, 3-POLE AC-3, 4KW/400V, SCREW TERMINALS AUXILIARY CONTACT 10E (1NO) AC OPERATION AC 110V 50/60HZ

| General details: | | | | | | |
|--|----|--------------|--|--|--|--|
| Size of the contactor | | 0 | | | | |
| Protection class IP / on the front | | IP20 | | | | |
| Ambient temperature / during operating | °C | 5525 | | | | |
| Reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750 | | к | | | | |
| Reference code / according to DIN EN 61346-2 | | Q | | | | |
| Main circuit: | | | | | | |
| Number of poles / for main current circuit | | 3 | | | | |
| Operating current / at AC-1 / at 400 V | | | | | | |
| • at 40 °C ambient temperature / rated value | А | 16 | | | | |
| Number of NC contacts / for main contacts | | 0 | | | | |
| Number of NO contacts / for main contacts | | 3 | | | | |
| Operating current / at AC-3 / at 400 V / rated value | А | 9 | | | | |
| Operating performance | | | | | | |
| • at AC-3 / at 400 V / rated value | kW | 4 | | | | |
| • at AC-1 / at 400 V / rated value | kW | 10 | | | | |
| Control circuit: | | | | | | |
| Design of activation / of the operating mechanism | | conventional | | | | |

| Voltage type / of control feed voltage | | AC |
|---|----|--|
| Control supply voltage frequency | | |
| • 1 / rated value | Hz | 50 |
| • 2 / rated value | Hz | 60 |
| Control supply voltage | | |
| • at 50 Hz / at AC / rated value | V | 110 |
| • at 60 Hz / at AC / rated value | V | 110 |
| Auxiliary circuit: | | |
| Number of NC contacts / for auxiliary contacts | | |
| lagging switching | | 0 |
| instantaneous switching | | 0 |
| Number of NO contacts / for auxiliary contacts | | |
| leading switching | | 0 |
| instantaneous switching | | 1 |
| Connection type: | | |
| Design of the electrical connection | | |
| for main current circuit | | screw-type terminals |
| for auxiliary and control current circuit | | screw-type terminals |
| Identification number and letter for switching elements | | 10 E |
| Mechanical design: | | |
| Mounting type | | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022 |
| Mounting type / series installation | | Yes |
| Width | mm | 45 |
| Height | mm | 48 |
| | | |

Certificates/approvals:

| General Product A | Approval | | | Functional Safety / Safety of Machinery | Test Certificates | | |
|---|----------|--------------------------------|------|---|-----------------------------|--|--|
| | (SA) | EAC | | Type Examination | Special Test Certificate | | |
| Shipping Approva | ıl | | | | | | |
| | GL | Lloyd's Kegister Lrs | RMRS | | | | |
| other | | | | | | | |
| Declaration of Conformity | other | Environmental Confirmations | | | | | |
| Further informati | on: | | | | | | |
| Information- and Downloadcenter (Catalogs, Brochures,) http://www.siemens.com/industrial-controls/catalogs | | | | | | | |
| Industry Mall (Online ordering system) http://www.siemens.com/industrial-controls/mall | | | | | | | |
| Cax online generator: http://www.siemens.com/cax | | | | | | | |
| Service&Support (Manuals, Certificates, Characteristics, FAQs,) http://support.automation.siemens.com/WW/view/en/3TF2010-0AG2/all | | | | | | | |
| Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams,) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TF2010-0AG2 | | | | | | | |

last change:

Jul 21, 2014