

# M4/8.SFD

[Print View..](#)  
[Print to Pdf..](#)

## General Information

<b>Extended Product Type:</b>	M4/8.SFD
<b>Product ID:</b>	1SNA115663R2300
<b>EAN:</b>	3472591156638
<b>Catalog Description:</b>	M4/8.SFD Screw Clamp Terminal Blocks - For 5 x 20 and 5 x 25 fuses - with blown fuse indicator - Grey
<b>Long Description:</b>	M4/8.SFD Screw Clamp Terminal Blocks Fuse



## Categories

Products » Low Voltage Products and Systems » Connection Devices »  
Terminal Blocks » Screw Clamp Terminal Blocks

## Ordering

<b>EAN:</b>	3472591156638
<b>Minimum Order Quantity:</b>	50 piece
<b>Customs Tariff Number:</b>	85361010

## Dimensions

<b>Product Net Width:</b>	8.0 mm
<b>Product Net Height:</b>	56.5 mm
<b>Product Net Depth:</b>	41.0 mm
<b>Product Net Weight:</b>	14.00 g

## Container Information

<b>Package Level 1 Units:</b>	50 piece
<b>Package Level 1 Width:</b>	101 mm
<b>Package Level 1 Height:</b>	47 mm
<b>Package Level 1 Length:</b>	265 mm
<b>Package Level 1 Gross Weight:</b>	0.70000 kg
<b>Package Level 1 EAN:</b>	3472591156638
<b>Package Level 2 Units:</b>	450 piece
<b>Package Level 2 Width:</b>	300 mm
<b>Package Level 2 Height:</b>	150 mm
<b>Package Level 2 Length:</b>	500 mm
<b>Package Level 2 Gross Weight:</b>	6.200 kg
<b>Package Level 3 Units:</b>	21600 piece
<b>Product Packing Type:</b>	Box

## Environmental

<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment
---------------------	---

## Technical UL/CSA

<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V
<b>Connecting Capacity-Main Circuit UL/CSA:</b>	Screw Clamp / Rigid 1x 22-12 AWG

**Connecting Capacity UL/CSA:** Screw Clamp / Rigid 22-12 AWG  
**Flammability According to UL94:** V0

---

### Additional Information

---

**Color:** Grey  
**Connecting Capacity-Main Circuit:** Screw Clamp / Flexible 1x 0.5-4 mm<sup>2</sup>  
Screw Clamp / Rigid 1x 0.5-6 mm<sup>2</sup>  
**Connection Type:** Screw clamp  
**Degree of Protection:** acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20  
**Function:** Fuse  
**Gauge Type:** A4  
**IIT Publishing Status:** Level 0 - Information enabled  
**Mounting on DIN Rail:** G32 (32 x 15 mm Mounting Rail) acc. to IEC 60715  
TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715  
TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715  
**Number of Levels:** 1  
**Pollution Degree:** 3  
**Product Main Type:** M4/8.SF  
**Product Name:** Terminal block  
**Rated Cross-Section:** 4 mm<sup>2</sup>  
**Rated Current (I<sub>n</sub>):** Main Circuit 6.3 A  
**Rated Impulse Withstand Voltage (U<sub>imp</sub>):** 4000 V  
**Rated Voltage (U<sub>r</sub>):** 400 V  
**Recommended Screw Driver:** 4 mm  
**RoHS Date:** 20050818  
**Spacing:** 8 mm  
**Sub-Function:** For 5x20 and 5x25 Fuses  
**Sub-Function 2:** With blown fuse indicator by LED 24V  
**Wire Stripping Length:** 9.5 mm

---

### Certificates and Declarations (Document Number)

---

**CSA Certificate:** TBD - OK in Ag.Base  
**cUL Certificate:** 1SND161002A0202  
**Declaration of Conformity - CE:** 1SND225007C1006  
**GOST Certificate:** 1SND161005A1104  
**RoHS Information:** 1SND230023F0206

---

### Classifications

---

**ETIM 4.0:** EC000899 - Fuse terminal block  
**ETIM 5.0:** EC000899 - Fuse terminal block  
**Object Classification Code:** X

---