

S7-1500 FRONT CONN. 40CORES H05V-K 2.5 M
 FRONT CONN. FOR SIMATIC S7-1500 40PIN (6ES7592-1AM00-0XB0) WITH 40 SINGLE CORES 0.5 MM² CORE TYPE H05V-K
 SCREW-TYPE VERSION L = 2.5M



Product properties, functions, components / general

Wire length	2.5 m
Color / of cable sheath	blue
Outer diameter / of cable sheath	2.2 mm
Conductor cross section / Rated value	0.5 mm ²
Number of channels	40
Number of poles	40

Operating data

Operating voltage / at DC	
<ul style="list-style-type: none"> Rated value maximum 	24 V 30 V
Continuous current / with simultaneous load on all cores / at DC / maximum permissible	1.5 A
Ambient temperature	
<ul style="list-style-type: none"> during storage during operation 	-30 ... +70 °C 0 ... 60 °C

General data

Certificate of suitability / cULus approval	No
---	----

Suitability for interaction	
<ul style="list-style-type: none"> • Input card PLC • PLC output card 	<p>Yes</p> <p>Yes</p>
Suitability for use	
<ul style="list-style-type: none"> • digital signal transmission • analog signal transmission 	<p>Yes</p> <p>No</p>
Equipment marking / acc. to DIN EN 81346-2	W
Net weight	1.28 kg