

# Product data sheet

Specifications



## Reverser block for vertical mounting, TeSys Ultra, 38A/690V, coil 110-240VAC/DC

LU2MB0FU

Product availability : Stock - Normally stocked in distribution facility

**Price\* : 192.00 USD**

### Main

Range	TeSys
Device short name	LU2MB
Product or Component Type	Reverser block
Device mounting	Direct mounting
Device Application	Motor control
[Ie] rated operational current	38 A
[Uc] control circuit voltage	110...240 V AC 50/60 Hz 110...220 V DC
Current consumption	1000 mA 110...220 V DC I maximum while closing 1000 mA 110...240 V AC I maximum while closing

### Complementary

[Ue] rated operational voltage	690 V AC power circuit
Network frequency	40...60 Hz
Inrush restraint duration	25 ms AC 15 ms DC
Operating time	150 ms with change of direction 75 ms without change of direction
Standards	EN 60947-6-2 IEC 60947-6-2 UL 60947-4-1, with phase barrier CSA C22.2 No 60947-4-1, with phase barrier
Product Certifications	CE UL CSA CCC EAC ASEFA ATEX Marine
[Ui] rated insulation voltage	690 V IEC 60947-6-2 600 V UL 60947-4-1 600 V CSA C22.2 No 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-6-2
Fixing mode	Plug-in
Connections - terminals	Control circuit screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (0.34...1.5 mm <sup>2</sup> ) 0.12 in (3 mm) flexible with cable end

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Control circuit screw clamp terminals 1 0.00...0.00 in<sup>2</sup> (0.75...1.5 mm<sup>2</sup>) 0.12 in (3 mm) flexible without cable end  
 Control circuit screw clamp terminals 1 0.00...0.00 in<sup>2</sup> (0.75...1.5 mm<sup>2</sup>) 0.12 in (3 mm) rigid  
 Control circuit screw clamp terminals 2 0.00...0.00 in<sup>2</sup> (0.34...1.5 mm<sup>2</sup>) 0.12 in (3 mm) flexible with cable end  
 Control circuit screw clamp terminals 2 0.00...0.00 in<sup>2</sup> (0.75...1.5 mm<sup>2</sup>) 0.12 in (3 mm) flexible without cable end  
 Control circuit screw clamp terminals 2 0.00...0.00 in<sup>2</sup> (0.75...1.5 mm<sup>2</sup>) 0.12 in (3 mm) rigid  
 Power circuit screw clamp terminals 1 0.00...0.02 in<sup>2</sup> (1...10 mm<sup>2</sup>) 0.16 in (4 mm) rigid  
 Power circuit screw clamp terminals 1 0.00...0.01 in<sup>2</sup> (1...6 mm<sup>2</sup>) 0.16 in (4 mm) flexible with cable end  
 Power circuit screw clamp terminals 1 0.00...0.02 in<sup>2</sup> (2.5...10 mm<sup>2</sup>) 0.16 in (4 mm) flexible without cable end  
 Power circuit screw clamp terminals 2 0.00...0.01 in<sup>2</sup> (1...6 mm<sup>2</sup>) 0.16 in (4 mm) flexible with cable end  
 Power circuit screw clamp terminals 2 0.00...0.01 in<sup>2</sup> (1...6 mm<sup>2</sup>) 0.16 in (4 mm) rigid  
 Power circuit screw clamp terminals 2 0.00...0.01 in<sup>2</sup> (1.5...6 mm<sup>2</sup>) 0.16 in (4 mm) flexible without cable end

<b>Tightening torque</b>	Control circuit 7.08...10.62 lbf.in (0.8...1.2 N.m) flat 0.20 in (5 mm) Control circuit 7.08...10.62 lbf.in (0.8...1.2 N.m) Philips No 2 0.20 in (5 mm) Power circuit 16.82...22.13 lbf.in (1.9...2.5 N.m) flat 0.24 in (6 mm) Power circuit 16.82...22.13 lbf.in (1.9...2.5 N.m) Philips No 2 0.24 in (6 mm)
<b>Width</b>	1.77 in (45 mm)
<b>Height</b>	3.15 in (80 mm)
<b>Depth</b>	4.13 in (105 mm)
<b>Net Weight</b>	0.88 lb(US) (0.4 kg)
<b>Compatibility code</b>	LU2MB

## Environment

<b>IP degree of protection</b>	IP20 IEC 60947-1 front panel and wired terminals) IP20 IEC 60947-1 other faces) IP40 IEC 60947-1 front panel outside connection zone)
<b>Protective treatment</b>	TH IEC 60068
<b>Ambient air temperature for operation</b>	-13...140 °F (-25...60 °C) with LUCM -13...158 °F (-25...70 °C) with LUCA, LUCB, LUCC, LUCD
<b>Ambient air temperature for storage</b>	-40...185 °F (-40...85 °C)
<b>Fire resistance</b>	1760 °F (960 °C) parts supporting live components IEC 60695-2-12 1202 °F (650 °C) IEC 60695-2-12
<b>Operating altitude</b>	6561.68 ft (2000 m)
<b>Shock resistance</b>	10 gn power poles open IEC 60068-2-27 15 gn power poles closed IEC 60068-2-27
<b>Vibration resistance</b>	2 gn 5...300 Hz) power poles open IEC 60068-2-27 4 gn 5...300 Hz) power poles closed IEC 60068-2-27
<b>Resistance to electrostatic discharge</b>	8 kV level 3, in open air IEC 61000-4-2 8 kV level 4, on contact IEC 61000-4-2
<b>Resistance to radiated fields</b>	9.14 V/m (10 V/m) level 3 IEC 61000-4-3
<b>Resistance to fast transients</b>	2 kV 3 serial link IEC 61000-4-4 4 kV 4 all circuits except for serial link IEC 61000-4-4
<b>Non-dissipating shock wave</b>	1 kV serial mode IEC 60947-6-2 2 kV common mode IEC 60947-6-2
<b>Immunity to radioelectric fields</b>	10 V IEC 61000-4-6

## Ordering and shipping details

<b>Category</b>	22399-TESYS U, ACCESSORIES
<b>Discount Schedule</b>	I11
<b>GTIN</b>	3389110363807
<b>Nbr. of units in pkg.</b>	1
<b>Package weight(Lbs)</b>	13.97 oz (396.0 g)
<b>Returnability</b>	Yes
<b>Country of origin</b>	FR

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.24 in (5.7 cm)
Package 1 width	3.74 in (9.5 cm)
Package 1 Length	5.12 in (13 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	12
Package 2 Weight	11.13 lb(US) (5.048 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	18 months
----------	-----------