



■ **产品材质:** A.C.E 部位采用 UL 认可的尼龙 PA66, B.D 部位采用丁腈橡胶。

■ **螺纹规格:** 公制(Metric), 德制(PG), 英制(G), 美制(NPT)。

■ **工作温度:** 静态 -40℃ 至 100℃, 瞬间耐热至 120℃, 动态 -20℃ 至 80℃, 瞬间耐热至 100℃。

■ **产品特性:** 特殊的夹紧爪与迫紧螺帽, 橡胶件设计, 可耐扭曲延长电缆寿命。夹紧电缆范围大, 抗拉力特强, 可防水, 防尘, 防盐, 耐酸碱, 酒精, 油脂及一般溶剂。

■ **颜色种类:** 黑色(RAL9005), 浅灰(RAL7035), 银色(RAL7001), 特殊颜色可定做。

■ **Material:** Parts A, C, E are made of UL approved nylon PA66, parts B and D are made of nitrile butadiene rubber (NBR).

■ **Thread spec.:** Metric, PG, G, NPT.

■ **Working temperature:** -40℃ to 100℃ in static state, instantaneous heat resistance up to 120℃; -20℃ to 80℃ in dynamic state, instantaneous heat resistance up to 100℃.

■ **Characteristics:** Special design of clamping die, sealing nut and rubber part, twisting resistance, prolonging cable life. Large range in clamping the cable, ultra-strong stretching resistance, waterproof, dustproof, and high ability to resist salt, acid, alkali, alcohol, grease and general solvent.

■ **Color:** Black(RAL9005), light grey (RAL7035), silver (RAL7001) as well as special colors that can be designed at request.



| 产品型号 Model | 螺纹规格 Thread Size | 适用电缆 Cable Range (mm) | 螺纹外径 Thread O. D. L2 (mm) | 螺纹长度 Thread Length L1 (mm) | 扳手直径 Spanner Size A & E (mm) | 数量 / 袋 Qty/bag |
|---------------|---------------------|-----------------------------|---------------------------------|----------------------------------|------------------------------------|-------------------|
| PG7-LR | PG7 | 3~6.5 | 12.5 | 15 | 18/16 | 100 |
| PG7-LR | PG7 | 2~5 | 12.5 | 15 | 18/16 | 100 |
| PG9-LR | PG9 | 4~8 | 15.2 | 15 | 22/19 | 100 |
| PG9-LR | PG9 | 2~6 | 15.2 | 15 | 22/19 | 100 |
| PG11-LR | PG11 | 5~10 | 18.6 | 15 | 24/22 | 100 |
| PG11-LR | PG11 | 3~7 | 18.6 | 15 | 24/22 | 100 |
| PG13.5-LR | PG13.5 | 6~12 | 20.4 | 15 | 27/24 | 50 |
| PG13.5-LR | PG13.5 | 5~9 | 20.4 | 15 | 27/24 | 50 |
| PG16-LR | PG16 | 10~14 | 22.5 | 15 | 30/27 | 50 |
| PG16-LR | PG16 | 7~12 | 22.5 | 15 | 30/27 | 50 |
| PG21-LR | PG21 | 13~18 | 28.3 | 15 | 35/33 | 50 |
| PG21-LR | PG21 | 9~16 | 28.3 | 15 | 35/33 | 50 |

| 产品型号 Model | 螺纹规格 Thread Size | 适用电缆 Cable Range (mm) | 螺纹外径 Thread O. D. L2 (mm) | 螺纹长度 Thread Length L1 (mm) | 扳手直径 Spanner Size A & E (mm) | 数量 / 袋 Qty/bag |
|---------------|---------------------|-----------------------------|---------------------------------|----------------------------------|------------------------------------|-------------------|
| M12-LR | M12x1.5 | 3~6.5 | 12 | 15 | 18/16 | 100 |
| M12-LR | M12x1.5 | 2~5 | 12 | 15 | 18/16 | 100 |
| M16-LR | M16x1.5 | 4~8 | 16 | 15 | 22/19 | 100 |
| M16-LR | M16x1.5 | 2~6 | 16 | 15 | 22/19 | 100 |
| M18-LR | M18x1.5 | 5~10 | 18 | 15 | 24/22 | 100 |
| M18-LR | M18x1.5 | 3~7 | 18 | 15 | 24/22 | 100 |
| M20-LR | M20x1.5 | 6~12 | 20 | 15 | 27/24 | 50 |
| M20-LR | M20x1.5 | 5~9 | 20 | 15 | 27/24 | 50 |
| M22-LR | M22x1.5 | 10~14 | 22 | 15 | 30/27 | 50 |
| M22-LR | M22x1.5 | 7~12 | 22 | 15 | 30/27 | 50 |
| M25-LR | M25x1.5 | 13~18 | 25 | 15 | 35/33 | 50 |
| M25-LR | M25x1.5 | 9~16 | 25 | 15 | 35/33 | 50 |
| M27-LR | M27x1.5 | 13~18 | 27 | 15 | 35/33 | 50 |
| M27-LR | M27x1.5 | 9~16 | 27 | 15 | 35/33 | 50 |