



NOTES

- 1 - 6X 4-40 UNC X (.125) TERMINAL SCREW AND LOCKWASHER
- 2 - ROLLER LEVER BRACKET ASSEMBLY MAY BE SET AT ANY POSITION AROUND AXIS OF PLUNGER
- 3 - SEAL RATING : NEMA 1.3
IP 54

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

CHARACTERISTICS	ELECTRICAL DATA
PRETRAVEL — .266 MAX	CONTACT ARRANGEMENT D P D T
DIFFERENTIAL TRAVEL — .165 MAX	
OVERTRAVEL — .219 MIN	
BASIC SWITCH REPLACEMENT — DT-2R3-A7	

L59 10A 125 OR 250 VAC
0.3A 125 VDC, 0.15A 250 VDC



THIRD ANGLE PROJECTION	
SCALE	FULL
DO NOT SCALE PRINT	
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
ONE PLACE	(.0) ±.030
TWO PLACE	(.00) ±.015
THREE PLACE	(.000) ±.005
ANGLES	±
WEIGHT	.71 LB

ANSI Y14.5M-1982 APPLIES