SIEMENS

Product data sheet

3TH2022-0AB0



CONTACTOR RELAY 22E EN 50 011 2NO+2NC, SCREW TERMINALS AC OPERATION AC 50HZ 24V/60HZ 29V

General details:					
Size of the contactor		0			
Ambient temperature					
during operating	°C	-25 +55			
Protection class IP / on the front		IP20			
Reference code					
 according to DIN 40719 extended according to IEC 204-2 / according to IEC 750 		К			
according to DIN EN 61346-2		К			
according to DIN EN 81346-2		К			
Control circuit:					
Voltage type / of control feed voltage		AC			
Control supply voltage frequency					
• 1	Hz	50			
• 2	Hz	60			
Control supply voltage					
• at 50 Hz / at AC / rated value	V	24			
• at 60 Hz / at AC / rated value	V	29			
Auxiliary circuit:					

Operating current /	at AC-15					
• at 230 V / rated v	value		А	4		
• at 400 V / rated v	value		А	3		
dentification numb	er and letter for swite	hing elements	_	22 E		
Number of NC conta	acts / for auxiliary co	ntacts		2		
 lagging switching]			0		
 delayed switching 	g			0		
 asynchronous sw 	vitching			0		
Number of NO contacts / for auxiliary contacts				2		
leading switching				0		
delayed switching				0		
asynchronous switching				0		
Number of changeover contacts / for auxiliary contacts				0		
Connection type:						
Design of the electrical connection / for auxiliary and control current circuit				screw-type terminals		
Mechanical desig	n:					
Mounting type			screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022			
Width			mm	45		
Height		mm	48			
Depth		mm	68			
Certificates/appro	ovals:					
General Product A	pproval				Functional Safety / Safety of Machinery	Declaration of Conformity
	SP CSA	EAC			Type Examination	EG-Konf.
Test Certificates			Shipping A	pproval		
other	Special Test Certificate	<u>Type Test</u> Certificates/Test Report	Lloyd's Register		RMRS	
other						
Declaration of Conformity	other	Environmental Confirmations				
Safety:						
Protection against electrical shock			finger-s	afe		
B10 value / with hig	h demand rate					

according to SN 31920		400,000				
• note		With 0.3 x le				
T1 value / for proof test interval or service life / according to IEC 61508	а	20				
Further information:						
Information- and Downloadcenter (Catalogs, Brochures,) http://www.siemens.com/industrial-controls/catalogs						
Industry Mall (Online ordering system) http://www.siemens.com/industrial-controls/mall						
Cax online generator http://www.siemens.com/cax						
Service&Support (Manuals, Certificates, Characteristics, FAQs,) http://support.automation.siemens.com/WW/view/en/3TH2022-0AB0/all						
Image database (product images, 2D dimension drawings, 3D mod http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TH202	•	ircuit diagrams,)				

last change:

Jun 16, 2014