

# Catalogue No: 1769-OB32

## COMPACTLOGIX 32DO 20.4-26.4V DC MODULE

Automation Systems > Modular Programmable Controllers > Compact PLC Systems > Allen-Bradley Bulletin 1769 CompactLogix™ > CompactLogix™ I/O Modules > CompactLogix™ Digital I/O Modules



### CompactLogix 32 Point 24V DC Output Module

- AC and DC modules available
- I/O density from 8 to 32 points per module
- Solid state and relay contact output modules available
- High speed input modules
- Input filtering is standard
- Optical isolation available

Representative Photo Only  
(actual product may vary based on configuration selections)

#### SPECIFICATIONS

Product Series	CompactLogix (Bul. 1768 / 1769)
Component Type PLC & I/O	Digital Output Module
Number of Digital Outputs	32 qty
Digital Output Type	24V DC Sourcing (NPN) type
Type, Digital Output	24V DC Source type
Digital Output Range	20.4 ... 26.4V DC
Rated Current per Digital Output, Max	0.5 A max, per DO
Rated Current per Module, Max	4 A max, per module
Operating Temperature, Max	60 °C max
Operating Temperature, Min	0 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
Humidity Type	Non-condensing

#### REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-