

Product datasheet

Specifications



Distribution block, Linergy DX, 4P, 63A, 4 modules, 24 holes, quick connection top

LVS04040

EAN Code: 3606482164567

Main

Range	Linergy
product or component type	Distribution block
Product name	Linergy DX
Range compatibility	Prisma PrismaSeT Pragma
Product compatibility	Spacial enclosures
IP degree of protection	IPxx B

Complementary

Location of connection	Top
mounting support	DIN rail
poles description	4P
[Ue] rated operational voltage	440 V AC
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	6 kV
[Ie] rated operational current	63 A at 40 °C
[In] rated current	63 A at 40 °C
Connections - terminals	Supply: tunnel type terminal16 mm ² (flexible) Supply: tunnel type terminal25 mm ² (rigid) Distribution: spring terminal (phase) , 12 x 2.5...6 mm ² (flexible) Distribution: spring terminal (phase) , 12 x 2.5...6 mm ² (rigid) Distribution: spring terminal (neutral) , 12 x 2.5...6 mm ² (flexible) Distribution: spring terminal (neutral) , 12 x 2.5...6 mm ² (rigid)
9 mm pitches	8
Total number of 18 mm modules	4
Height	96.5 mm
Width	72 mm
Depth	62 mm
net weight	0.29 kg

Environment

Pollution degree	3
Resistance to incandescent wire	960 °C conforming to IEC 60695-2-11

Standards	IEC 60947-7-1 IEC 61439-2 IEC 61439-1
------------------	---

Product certifications	ASEFA
-------------------------------	-------

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Number of Units in Package 1	1
-------------------------------------	---

Package 1 Height	7.5 cm
-------------------------	--------

Package 1 Width	7.5 cm
------------------------	--------

Package 1 Length	10.5 cm
-------------------------	---------

Package 1 Weight	328.0 g
-------------------------	---------

Unit Type of Package 2	S03
-------------------------------	-----

Number of Units in Package 2	30
-------------------------------------	----

Package 2 Height	30.0 cm
-------------------------	---------

Package 2 Width	30.0 cm
------------------------	---------

Package 2 Length	40.0 cm
-------------------------	---------

Package 2 Weight	10.148 kg
-------------------------	-----------

Contractual warranty

Warranty	18 months
-----------------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

✔ Toxic Heavy Metal Free

✔ Mercury Free

✔ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)
