

Product datasheet

Specifications



Magnetic latching contactor, TeSys F, 3P(3NO), AC-3 <=440V 630A, 220V DC coil with low inrush consumption

CR1F630MZ7

(!) Discontinued

(!) Discontinued on: 9 Feb 2023

Main

Range	TeSys
Product name	TeSys F
Product or component type	Magnetic latching contactor
Device short name	CR1F
Device application	Control
contactor application	Resistive load Motor control
Utilisation category	AC-4 AC-1 AC-3
poles description	3P
power pole contact composition	3 NO
[Ue] rated operational voltage	1000 V AC 25...200 Hz
[Ie] rated operational current	630 A (at <40 °C) at <= 440 V AC AC-3 1000 A (at <40 °C) at <= 440 V AC AC-1 560 A (at <40 °C) at <= 440 V AC AC-4
Motor power kW	335 kW at 400 V AC 50/60 Hz (AC-4)
Control circuit type	DC low consumption
[Uc] control circuit voltage	220 V DC
Irms rated making capacity	6740 A
Rated breaking capacity	6300 A at 220...440 V 5400 A at 500 V 3200 A at 1000 V 4600 A at 660/690 V
[Icw] rated short-time withstand current	5.05 kA 40 °C - 1 s 5.05 kA 40 °C - 5 s 5.05 kA 40 °C - 10 s 4400 A 40 °C - 30 s 3400 A 40 °C - 1 min 2200 A 40 °C - 3 min 1600 A 40 °C - 10 min
Associated fuse rating	630 A aM at <= 440 V 1000 A BS88 at <= 440 V 1000 A gG at <= 440 V
Average impedance	0.12 mOhm - lth 1000 A 50 Hz
[Ui] rated insulation voltage	1000 V conforming to IEC 60158-1 1000 V conforming to IEC 60947-4 1000 V conforming to BS 775 1500 V conforming to VDE 0110 group C

Power dissipation per pole	48 W AC-3 120 W AC-1
Standards	EN/IEC 60947-1 EN/IEC 60947-4-1 JIS C8201-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
product certifications	CB Scheme UL CSA EAC CE UKCA
Connections - terminals	Bars 2 cable(s) - busbar cross section: 60 x 5 mm Power circuit: bolted connection
Tightening torque	58 N.m
Operating time	40...80 ms latching 50...100 ms unlatching
Mechanical durability	1 Mcycles
Maximum operating rate	120 cyc/h 40 °C

Complementary

Control circuit voltage limits	Latching: 0.85...1.1 Uc Unlatching: 0.85...1.1 Uc
average consumption	620 W DC latching 45 W DC unlatching

Environment

Protective treatment	TC
Ambient air temperature for operation	-15...70 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating
Height	304 mm
Width	309 mm
Depth	255 mm
Net weight	18.6 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.5 cm
Package 1 Width	34.0 cm
Package 1 Length	35.0 cm
Package 1 Weight	16.37 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

 Mercury Free

 RoHS Exemption Information Yes

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu RoHS Directive

Compliant with Exemptions

China RoHS Regulation

[China RoHS declaration](#)

Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

[End of Life Information](#)