



EasyPact TVS contactor 3P(3 NO) - AC-3 - <= 440 V 250A - 240 V AC coil

LC1E250U5

Main

Range	Easy TeSys	
Range of product	Easy TeSys Control	
Product or component type	Contactor	
Device short name	LC1E	
Contactor application	Motor control Resistive load	
Utilisation category	AC-3 AC-3e AC-1	
Poles description	3P	
[Ue] rated operational voltage	Power circuit: <= 690 V AC 50/60 Hz	
[le] rated operational current	250 A (at <55 °C) at <= 440 V AC AC-3 for power circuit 190 A (at <55 °C) at <= 440 V AC AC-3e for power circuit 300 A (at <40 °C) at <= 440 V AC AC-1 for power circuit	
[Uc] control circuit voltage	240 V AC 50 Hz	

Complementary

Complementary	
Motor power kW	75 kW at 220230 V AC 50/60 Hz 132 kW at 380400 V 140 kW at 415 V 140 kW at 440 V 160 kW at 500 V 160 kW at 660690 V
Pole contact composition	3 NO
[Ith] conventional free air thermal current	300 A (at 40 °C) for power circuit
Irms rated making capacity	2500 A at 440 V AC for power circuit conforming to IEC 60947-4-1
Rated breaking capacity	2000 A at 440 V for power circuit conforming to IEC 60947
[lcw] rated short-time withstand current	1800 A 40 °C - 10 s for power circuit
Associated fuse rating	10 A gG at <= 690 V coordination type 1 for control circuit conforming to IEC 60947-5-1 315 A gG at <= 690 V coordination type 1 for power circuit
Average impedance	0.32 mOhm - Ith 300 A 50 Hz for power circuit
Power dissipation per pole	20 W AC-3 29 W AC-1
[Ui] rated insulation voltage	690 V conforming to IEC 60947-4-1
Overvoltage category	III
Pollution degree	3

[Uimp] rated impulse withstand voltage	8 kV coil not connected to the power circuit conforming to IEC 60947
Mechanical durability	5000000 cycles
Electrical durability	200000 cycles AC-1 700000 cycles AC-3
Control circuit type	AC at 50 Hz
Control circuit voltage limits	0.851.1 Uc (-555 °C):operational 50 Hz 0.350.55 Uc (-555 °C):drop-out 50 Hz
Inrush power in VA	805 VA 50 Hz cos phi 0.3 (at 20 °C) 970 VA 60 Hz cos phi 0.3 (at 20 °C)
Hold-in power consumption in VA	55 VA 50 Hz cos phi 0.3 (at 20 °C) 66 VA 60 Hz cos phi 0.3 (at 20 °C)
Heat dissipation	1824 W for control circuit
Operating time	2035 ms on closing 715 ms on opening
Maximum operating rate	1200 cyc/h 55 °C
Connections - terminals	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: flexible with cable end Power circuit: cable with lug - external diameter: 185 mm Power circuit: bars 2 - busbar cross section: 32 x 4 mm
Tightening torque	Control circuit: 1.2 N.m Power circuit: 35 N.m
Minimum switching voltage	17 V for control circuit
Minimum switching current	5 mA for control circuit
Insulation resistance	> 10 MOhm for control circuit
Non-overlap time	1.5 ms on energisation guaranteed between NC and NO contact 1.5 ms on de-energisation guaranteed between NC and NO contact
Mounting support	Plate
Environment	
Standards	IEC 60947-1 IEC 60947-4-1 IEC 60947-5-1
Product certifications	EAC CE
IP degree of protection	IP00 conforming to IEC 60529
Permissible ambient air temperature around the device	-2070 °C at Uc -6080 °C storage -555 °C operation
Operating altitude	3000 m without derating
Fire resistance	850 °C conforming to IEC 60695-2-1
Mechanical robustness	Vibrations contactor open (1.5 Gn, 5300 Hz) Vibrations contactor closed (3 Gn, 5300 Hz) Shocks contactor open (6 Gn for 11 ms) Shocks contactor closed (7 Gn for 11 ms)

Height	197 mm
Width	168.5 mm
Depth	181 mm
Net weight	4.7 ka

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21.5 cm
Package 1 Width	24.0 cm
Package 1 Length	26.0 cm
Package 1 Weight	5.4 kg
Unit Type of Package 2	S06
Number of Units in Package 2	12
Package 2 Height	73.5 cm
Package 2 Width	60.0 cm
Package 2 Length	80.0 cm
Package 2 Weight	77.8 kg

Contractual warranty

Warranty 18 months

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >







Sustainable Packaging Transparency RoHS/REACh

Resource performance



Sustainable Packaging

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

7 Nov 2024

Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



Technical Illustration

Assembly's dimensions



