

Plug-in module - RIF-LV-120-230 AC/110 DC - 2900944

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in module, for mounting on RIF-1, RIF-2, RIF-3, and RIF-4, with varistor and yellow LED, input voltage: 120 ... 230 V AC/110 V DC ± 20 %



Key Commercial Data

Packing unit	10 pc
GTIN	 4 046356 733250
GTIN	4046356733250

Technical data

Input data

Nominal input voltage U_N	110 V DC ± 20 %
Input voltage range	120 V AC ... 230 V AC ± 20 %
Status display	Yellow LED
Protective circuit/component	Varistor

Standards and Regulations

Connection in acc. with standard	CSA
----------------------------------	-----

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Plug-in module - RIF-LV-120-230 AC/110 DC - 2900944

Approvals

Approvals

DNV GL / CSA / PRS / LR / UL Recognized / EAC

Ex Approvals

Approval details

DNV GL		http://exchange.dnv.com/tari/	TAA000018V
CSA		http://www.csagroup.org/services-industries/product-listing/	2607057
PRS		http://www.prs.pl/	TE/2108/880590/16
LR		http://www.lr.org/en	15/20011
UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 113228
EAC			RU C- DE.A*30.B.01082