

General Information

Extended Product Type:	CA5X-01
Product ID:	1SBN019010R1001
EAN:	3471522387912
Catalog Description:	CA5X-01 Auxiliary contact block
Long Description:	CA5X-01 Auxiliary Contact Block

Additional Information

ABB Industrial IT Suite:	Control IT
CB Certificate:	CB_CN28662
CCC Certificate:	CCC_2013010304656838
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-5-1, q = 40 °C 16 A
Country of Origin:	India (IN)
Customs Tariff Number:	85030099
Data Sheet, Technical Information:	1SXF101004C2001
Declaration of Conformity - CE:	1SBD250013U1000
EAN:	3471522387912
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SBB910513D4501
Invoice Description:	CA5X-01 Auxiliary contact block
Maximum Electrical Switching Frequency:	AC-15 1200 cycles per hour DC-13 900 cycles per hour
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Minimum Order Quantity:	10 piece
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	0
Object Classification Code:	K
Package Level 1 EAN:	3471522387912
Package Level 1 Gross Weight:	0.14 kg
Package Level 1 Height:	40 mm
Package Level 1 Length:	130 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	65 mm
Package Level 2 Height:	300 mm
Package Level 2 Length:	380 mm
Package Level 2 Units:	600 piece
Package Level 2 Width:	220 mm
Packing Type:	Box
Product Main Type:	Accessories for Block Contactors
Product Name:	Auxiliary Contact Block
Product Net Depth:	47 mm
Product Net Height:	36 mm
Product Net Weight:	0.013 kg
Product Net Width:	10 mm

Product Net Weight:	10 mm
Product Packing Type:	Box
Rated Insulation Voltage (U_i):	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
Rated Operational Current AC-15 (I_e):	(220 / 240 V) 4 A (24 / 127 V) 6 A (690 V) 2 A (380 / 440 V) 3 A
Rated Operational Current DC-13 (I_e):	(110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.30 A / 66 W (24 V) 6 A / 144 W (250 V) 0.30 A / 75 W (400 V) 2.8 A / 134 W (500 V) 1 A / 72 W
Rated Operational Voltage:	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Short-time Withstand Current (I_{cw}):	for 0.1 s 140 A for 1 s 100 A
Selling Unit of Measure:	piece
Short Description:	CA5X-01 Auxiliary contact block
Suitable For:	AX06 AX09 AX12 AX18 AX25 AX32 AX40 AX50 AX65 AX80 AX95 AX115 AX150 NX
Terminal Type:	Screw Terminals
UNSPSC:	39121500



